

Overall Dimensions and performance parameters of DCL-Ex40/60 Explosion proof Type

Explosion-proof standard type

Explosion-proof Direct Installation Type

Type Power Performance Parameters	DCL—Ex40			DCL—Ex60					
	AC110V	AC380V	AC220V	AC110V	AC380V	AC220V			
Motor Power	90W	40W	90W	90W	40W	90W			
Rated Current	1.12A	0.29A	0.64A	1.18A	0.29A	0.67A			
Standard Time/Torque	30S/400Nm			45S/600Nm					
Optional Time/Torque	15S/200Nm		15S/200Nm 60S/400Nm						
Turning Angle	0 ~ 90° Adjustable								
Available Control Circuit	Types of A、B、C、D、E、F、H								
Total Weight	9.5kg			10.0kg					
Insulating Resistance	AC110V/AC220V/AC380V：100 MΩ/500VDC								
Withstand Voltage Class	AC110V/AC220V:1500VAC 1minutes、AC380V:1800VAC 1minutes								
Protection Class	IP67								
Explosive-proof grade	Exd II BT4								
Installation Angle	360° at any angle								
Electric Interface	2-G1/2 explosion-proof plug ,clients should install corresponding explosion-proof cable connector when using according to the cable selected.								
Ambient Temperature	-20℃ ~ +60℃								
Optional Function	◆Over-torque Protector ◆Heater for eliminating moisture								

Explosion-proof standard type

Explosion-proof Direct Installation Type

